

The Universal basement drain DN 100, Black grating, Backwater protection



Article information

Item no.: 27611
GTIN: 4026092007822
Price group: 10

Advantages

- Flexible installation: vertically adjustable upper section rotatable
- tiltable
- vertically adjustable
- standard inlets
- Integrated backwater protection
- Flexible planning thanks to three fixed

Description

The basement drain with three standard inlets (2x DN 50 / 1x DN 70) for faecal-free wastewater is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves at the same time as an emergency closure to be closed by hand.

Type of wastewater: wastewater without sewage
Installation situation: floor slab installation

Version:

Odour trap: included
Emergency closure: yes
Delivery state: installation-ready
Backwater protection: Type 5
Number of mechanical backwater flaps: 2

General characteristics:

Nominal size (DN): 100
Outer diameter (OD): 110
Colour: black
Standard: EN 1253, EN 13564

Dimensions:

Length:	380 mm
Width:	300 mm
Cutout dimension, length:	400 mm
Cutout dimension, width:	320 mm

Tank:

Installation depth:	216 - 276 mm
---------------------	--------------

Drain body:

Socket version:	lateral
Vertical adjustment:	vertically adjustable upper section

Coverage features:

Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Load class:	K 3 (EN 1253-1)
Sludge bucket:	yes

Grating:

Grid size, width:	188 mm
Grid size, height:	25 mm
Grid size, length:	188 mm