


Submersible pump Aquadive KTP 300 without float switch, 10 m



Article information

Item no.: 28740
 GTIN: 4026092000908
 Price group: 20

Description

KTP 300 submersible pump without float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

Type of wastewater: wastewater without sewage

General characteristics:

Material: Polymer
 Standard: EN 12050-2

Dimensions:

Length: 275 mm
 Width: 390 mm
 Height: 216 mm

Pressure pipe connection: R 1"
 Free passage: 10 mm

Pumping device:

Pump: KTP 300
 Number of pumps: 1

Max. pumping capacity:	8 m ³ /h
Max. pumping height:	6 m
Operating voltage:	230 V
Mains frequency:	50 Hz
Operating mode:	S1
Power P1:	0.34 kW
Power P2:	0.21 kW
Speed:	2,800 U/min
Type of fuse required (electrical protection):	C 16 A
Max. temperature (permanent) of conveyed material:	40 °C
Connection type:	Schuko (earthed contact) 2-pin
Weight:	4 kg
Impeller type:	Multi-vane impeller
Length of mains cable for pump:	10 m
Rated current:	1.6 A
Protection class (pump):	IP 68 (3m)
Protection class:	I
Type of pump connection cable:	H07RN-F 3G 1.0 mm ²
Temperature monitoring:	integrated
Insulation class:	F
Cable length:	10 m