

## Submersible pump Aquadive STZ 1000 resistant, without float switch, 10 m



### Article information

Item no.: 28779  
GTIN: 4026092055885  
Price group: 20

### Description

Replacement pump Aquadive without ATEX, with macerator, without float control.  
Type of wastewater: wastewater with sewage

### General characteristics:

Material: Polymer  
Standard: EN 12050-1

### Dimensions:

Length: 258 mm  
Width: 258 mm  
Height: 294 mm

Pressure pipe connection: R 1 1/4"

### Pumping device:

Pump: STZ 1000  
Number of pumps: 1  
Max. pumping capacity: 11.5 m<sup>3</sup>/h  
Max. pumping height: 10 m  
Operating voltage: 230 V  
Mains frequency: 50 Hz  
Operating mode: S3 - 30 %  
Power P1: 1.2 kW  
Power P2: 0.69 kW  
Speed: 2,800 U/min  
Type of fuse required (electrical protection): C 16 A

|  |                                |
|--|--------------------------------|
| Max. temperature (permanent) of conveyed material: | 40 °C                          |
| Connection type:                                   | coded plug                     |
| Weight:  | 10 kg                          |
| Impeller type:                                     | Macerator                      |
| Length of mains cable for pump:                    | 10 m                           |
| Rated current:                                     | 4.9 A                          |
| Protection class (pump):                           | IP 68 (3m)                     |
| Protection class:                                  | I                              |
| Type of pump connection cable:                     | H07RN-F 3G 1.0 mm <sup>2</sup> |
| Temperature monitoring:                            | integrated                     |
| Cos phi - power factor:                            | 0.97                           |
| Insulation class:                                  | F                              |
| Cable length:                                      | 10 m                           |