


## Submersible pump Aquadive KTP 300 resistant, with float switch, 10m



### Article information

Item no.: 28840C  
 GTIN: 4026092093634  
 Price group: 20

### Description

KTP 300 submersible pump with float switch, with non-return flap, pivoted connection, removable intake cage; the water level can be lowered to 8 mm.

Type of wastewater: wastewater without sewage

### Version:

Pump control:	Float switch
Backflow preventer:	integrated
Resistant:	Resistant to saline media, wastewater from water softening systems and wastewater containing condensate from heating systems

### Dimensions:

Length:	275 mm
Width:	390 mm
Height:	216 mm

Pressure pipe connection:	R 1"
Free passage:	10 mm

**Pumping device:**

Number of pumps:	1
Max. pumping capacity:	8 m <sup>3</sup> /h
Max. pumping height:	6 m
Operating voltage:	230 V
Mains frequency:	50 Hz
Operating mode:	S1
Power P1:	0.34 kW
Power P2:	0.21 kW
Speed:	2,800 U/min
Type of fuse required (electrical protection):	C 16 A
Max. temperature (permanent) of conveyed material:	40 °C
Connection type:	Schuko (earthed contact) 2-pin
Weight:	4 kg
Impeller type:	Multi-vane impeller
Length of mains cable for pump:	10 m
Rated current:	1.9 A
Protection class (pump):	IP 68
Protection class:	I
Type of pump connection cable:	H07RN-F 3G 1.0 mm <sup>2</sup>
Insulation class:	F

**Control:**

Type of level measurement:	mechanical
----------------------------	------------