


Submersible pump Aquadive GTF 1000 with float switch, 10m



Article information

Item no.: 28860
 GTIN: 4026092044513
 Price group: 20

Description

Submersible pump for faecal-free wastewater,
 type KTP 1000, new designation:
 Type of wastewater:

GTF 1000

wastewater without sewage

Version:

Pump control:

Float switch

General characteristics:

Material:
 Standard:

Polymer
 EN 12050-2

Dimensions:

Length: 195 mm
 Width: 195 mm
 Height: 290 mm

Pressure pipe connection: R 1 1/4"
 Free passage: 10 mm

Pumping device:

| | |
|--|--------------------------------|
| Pump: | GTF 1000 |
| Number of pumps: | 1 |
| Max. pumping capacity: | 14 m ³ /h |
| Max. pumping height: | 10 m |
| Operating voltage: | 230 V |
| Mains frequency: | 50 Hz |
| Operating mode: | S3 - 50 % |
| Power P1: | 1.3 kW |
| Power P2: | 0.75 kW |
| Speed: | 2,700 U/min |
| Type of fuse required (electrical protection): | C 16 A |
| Max. temperature (permanent) of conveyed material: | 40 °C |
| Connection type: | coded plug |
| Weight: | 10 kg |
| Impeller type: | Multi-vane impeller |
| Length of mains cable for pump: | 10 m |
| Rated current: | 5.6 A |
| Protection class (pump): | IP 68 (3m) |
| Protection class: | I |
| Type of pump connection cable: | H07RN-F 3G 1.0 mm ² |
| Temperature monitoring: | integrated |
| Cos phi - power factor: | 0.97 |
| Insulation class: | F |
| Cable length: | 10 m |

Control:

| | |
|----------------------------|------------|
| Type of level measurement: | mechanical |
|----------------------------|------------|