


Submersible pump Aquadive GTF1000 resistant, without float switch, 10 m



Article information

Item no.: 28860C
GTIN: 4026092093771
Price group: 20

Description

Submersible pump for faecal-free wastewater
Type of wastewater:

wastewater without sewage

Version:

Pump control:
Resistant:

Float switch
Resistant to saline media, wastewater from water softening systems and wastewater containing condensate from heating systems

Dimensions:

Length: 195 mm
Width: 195 mm
Height: 290 mm

Pressure pipe connection: R 1 1/4"
Free passage: 10 mm

Pumping device:

Pump:	GTF 1000 resistant
Max. pumping capacity:	14 m ³ /h
Max. pumping height:	10 m
Operating voltage:	230 V
Mains frequency:	50 Hz
Operating mode:	S3 - 50 %
Power P1:	1.3 kW
Power P2:	0.75 kW
Speed:	2,700 U/min
Type of fuse required (electrical protection):	C 16 A
Max. temperature (permanent) of conveyed material:	40 °C
Connection type:	coded plug
Weight:	10 kg
Impeller type:	Multi-vane impeller
Length of mains cable for pump:	10 m
Rated current:	5.6 A
Protection class (pump):	IP 68 (3m)
Protection class:	I
Type of pump connection cable:	H07RN-F 3G 1.0 mm ²
Insulation class:	F

Control:

Type of level measurement:	mechanical
----------------------------	------------