

Basement drain DN 100, Black grating, Class K 3



Article information

Item no.: 29111
GTIN: 4026092007846
Price group: 10

Advantages

- Integrated odour trap
- Including sludge bucket

Description

The basement drain made of polymer for floor slab installation is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

Version:

Odour trap:	included
Position of lateral connection:	Type II
Sealing water height:	60 mm

General characteristics:

Nominal size (DN):	100
Outer diameter (OD):	110
Standard:	EN 1253-1

Dimensions:

Length:	380 mm
Width:	290 mm
Cutout dimension, length:	400 mm
Cutout dimension, width:	320 mm

Tank:

Number of inlets:	2 ST
Inlet nominal size (DN):	70
Installation depth:	216 - 276 mm

Drain body:

Material of drain body:	PP
Socket version:	lateral
Vertical adjustment:	vertically adjustable upper section
Vertical adjustment:	30 - 90 mm

Coverage features:

Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Load class:	K 3 (EN 1253-1)
Length:	188 mm
Width:	188 mm
Sludge bucket:	yes
Locking:	placed

Grating:

Rim length:	200 mm
Rim width:	200 mm
Rim material:	Polymer
Upper section material:	Polymer
Discharge rate (l/s) with 20 mm backwater:	1.8 l/s