

Practicus basement drain DN 100, Black grating, Vertical outlet



Article information

Item no.: 34102
GTIN: 4026092047705
Price group: 10

Advantages

- Vertically adjustable upper section
- Suitable for floor slab installation

Description

The Practicus basement drain is made of polymer and is suitable for floor slab installation. The upper section with slotted grating is vertically adjustable.

Version:

Odour trap: no

General characteristics:

Nominal size (DN): 100
Outer diameter (OD): 110
Standard: EN 1253-2

Dimensions:

Length: 150 mm
Width: 150 mm
Cutout dimension, length: 180 mm
Cutout dimension, width: 180 mm

Tank:

Number of outlets: 1 ST
Installation depth: 221 - 277 mm

Drain body:

Material of drain body: Polymer

Socket version:	vertical
Vertical adjustment:	vertically adjustable upper section

Coverage features:

Type of cover:	Slotted cover
Cover material:	Polymer
Colour of cover:	black
Load class:	K 3 (EN 1253-1)
Length:	138 mm
Width:	138 mm
Sludge bucket:	yes
Locking:	placed

Grating:

Rim material:	Polymer
Upper section material:	Polymer
Discharge rate (l/s) with 10 mm backwater:	1,1 l/s
Discharge rate (l/s) with 20 mm backwater:	1.8 l/s