


## Shower chan. Linearis Infinity 60 L: 900 mm, DN 40, Polished SST





## **Article information**

Item no.: 45101.09 GTIN: 4026092093986

Price group: 10

## Description

The narrow Linearis Infinity channel for walk-in showers is suitable for indoor linear drainage for household and commercial use. The channel profile made of 316 stainless steel can be extended straight or at three (30, 45 and 90 degree) angles.

The drain body made of PP is equipped with sound and settlement absorbers. The channel contains a clip-on flange with factory-mounted waterproofing membrane to EN 1253-1 and

DIN 18534-1-W3-I. The channel profile can be pushed in the lengthwise and transverse direction in the clip-on flange to level out construction tolerance.

Including odour trap with 24 mm water seal.

Open seepage water openings, without flooding of the waterproofing level in the event of backwater.

## Version:

Odour trap: with 24 mm water seal

Type of waterproofing layer: Factory-fitted sealing collar (WaD) according to DIN

18534

W3-I

Seepage opening: open

Water exposure class in accordance to DIN

18534-1 (up to and including):

Sealing water height: 24 mm



Dimensions:	
Length: Width: Min. design height:	264 mm 111 mm 60 mm
Tank:	
Outlet nominal size (DN): Outlet nominal size (OD):	40 40
Drain body:	
Material of drain body: Socket version:	PP lateral
Coverage features:	
Type of cover: Cover material: Min. flooring height: Max. flooring height: Load class: Length: Width: Surface: Locking:	Stainless steel cover 316 stainless steel 11 mm 25 mm K 3 (EN 1253-1) 900 mm 45 mm Polished SST placed
Shape of upper section: Discharge rate (l/s) with 10 mm backwater:	square 0.4 l/s

Discharge rate (l/s) with 20 mm backwater:

40

**General characteristics:** 

Nominal size (DN):

 $0.5 \, l/s$