


## Shower chan. Linearis Infinity 90 L: 1200 mm, DN50, Copper, brushed





## **Article information**

Item no.: 45203.12 GTIN: 4026092094426

Price group: 10

## **Description**

The narrow Linearis Infinity channel for walk-in showers is suitable for indoor linear drainage for household and commercial use. The channel profile made of 316 stainless steel can be extended straight or at three (30, 45 and 90 degree) angles.

The drain body made of PP is equipped with sound and settlement absorbers. The channel contains a clip-on flange with factory-mounted waterproofing membrane to EN 1253-1 and

DIN 18534-1-W3-I. The channel profile can be pushed in the lengthwise and transverse direction in the clip-on flange to level out construction tolerance.

Including odour trap with 50 mm water seal.

Open seepage water openings, without flooding of the waterproofing level in the event of backwater.

## Version:

Odour trap: with 50 mm water seal

Type of waterproofing layer: Factory-fitted sealing collar (WaD) according to DIN

18534

Water exposure class in accordance to DIN

18534-1 (up to and including):

W3-I



| Sealing water height:  | 50 mm   |
|--|---|
| General characteristics:   |   |
| Nominal size (DN):   | 50  |
| Dimensions:  |   |
| Length:<br>Width:<br>Min. design height:   | 264 mm<br>111 mm<br>90 mm   |
| Tank:  |   |
| Outlet nominal size (DN): Outlet nominal size (OD):  | 50<br>50  |
| Drain body:  |   |
| Material of drain body:<br>Socket version:   | PP<br>lateral   |
| Coverage features:   |   |
| Type of cover: Cover material: Min. flooring height: Max. flooring height: Load class: Length: Width: Surface: | Stainless steel cover 316 stainless steel 11 mm 25 mm K 3 (EN 1253-1) 1,200 mm 45 mm Copper brushed |
| Locking:   | placed  |

Shape of upper section:

Discharge rate (l/s) with 10 mm backwater:

Discharge rate (l/s) with 20 mm backwater:

square

0.6 l/s

0.8 l/s