


Shower chan. Linearis Infinity 60 L: 1100 mm, DN 40, Black, br., Megastop





Article information

Item no.: 45302.11 GTIN: 4026092094310

Price group: 10

Description

The narrow Linearis Infinity channel for walk-in showers is suitable for indoor linear drainage for household and commercial use. The channel profile made of 316 stainless steel can be extended straight or at three (30, 45 and 90 degree) angles.

The drain body made of PP is equipped with sound and settlement absorbers. The channel contains a clip-on flange with factory-mounted waterproofing membrane to EN 1253-1 and

DIN 18534-1-W3-I. The channel profile can be pushed in the lengthwise and transverse direction in the clip-on flange to level out construction tolerance.

Including Megastop mechanical odour trap with water seal.

Open seepage water openings, without flooding of the waterproofing level in the event of backwater.

Version:

Odour trap: Megastop (mechanical)

Type of waterproofing layer: Factory-fitted sealing collar (WaD) according to DIN

18534

Water exposure class in accordance to ${\sf DIN}$

18534-1 (up to and including):

W3-I



| Dimensions: | |
|--|-----------------------------|
| Length: | 264 mm |
| Width: | 111 mm 60 mm |
| Min. design height: | OO IIIIII |
| | |
| Tank: | |
| Outlet nominal size (DN): | 40 |
| Outlet nominal size (OD): | 40 |
| | |
| Drain body: | |
| Material of drain body: | PP |
| Socket version: | lateral |
| | |
| Coverage features: | |
| Type of cover: | Stainless steel cover |
| Cover material: | 316 stainless steel |
| Min. flooring height: | 11 mm |
| Max. flooring height: | 25 mm |
| Load class: | K 3 (EN 1253-1) 1,100 mm |
| Length: Width: | 45 mm |
| Surface: | Black brushed |
| Locking: | placed |
| Chang of upper continu | aguara |
| Shape of upper section: Discharge rate (I/s) with 10 mm backwater: | square 0.2 l/s |
| Discharge rate (I/s) with 20 mm backwater: | 0.4 l/s |
| | · , - |

40

General characteristics:

Nominal size (DN):