

Upper section, Linearis Compact L: 1050 mm, Sys 100, 304 SST cover, K 3



Article information

Item no.: 47811S
 GTIN: 4026092079959
 Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Low installation depth
- Highest fire protection standards

Description

Used in combination with a drain body of the KESSEL 100 modular system, the Linearis Compact upper section is suitable for use as indoor linear drainage.

Version:

System:	100
Odour trap:	included
Type of waterproofing layer:	Waterproofing layer
Seepage opening:	yes
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I
Sealing water height:	50 mm

General characteristics:

Nominal size (DN):	100
Outer diameter (OD):	100

Dimensions:

Width:	136 mm
Height:	77 mm
null:	1,115 mm

Coverage features:

Type of cover:	Stainless steel cover
Grating design:	optionally tileable
Cover material:	304 stainless steel
Colour of cover:	silver, selectable
Load class:	K 3 (EN 1253-1)
Locking:	placed

Grating:

Rim length:	1,050 mm
Rim width:	66 mm
Rim material:	304 stainless steel

Upper section material:	ABS
Discharge rate (l/s) with 10 mm backwater:	0.6 l/s
Discharge rate (l/s) without backwater:	0.5 l/s