


Ecoguss project drain DN 80, horizontal, Slotted cover



Article information

Item no.: 48383.11
 GTIN: 4026092034309
 Price group: 40

Advantages

- High-tech Ecoguss composite material
- Highest fire protection standards
- Scientifically confirmed sound protection effect

Description

The Ecoguss project drain with connection flange is used for point drainage and is equipped with a removable odour trap as well as a lip seal and a temporary protective cover.

The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius.

The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Version:

System:	125
Odour trap:	included
Waterproofing layer on the upper section:	Connection flange
Waterproofing layer on the drain body:	Connection flange
Sealing water height:	50 mm

General characteristics:

Nominal size (DN):	80
Outer diameter (OD):	83
Standard:	EN 1253-1

Tank:

Number of outlets:	1 ST
--------------------	------

Drain body:

Material of drain body:	Ecoguss
Socket version:	lateral

Vertical adjustment:	vertically adjustable upper section
Upper section:	vertically adjustable

Coverage features:

Type of cover:	Slotted cover
Cover material:	304 stainless steel
Colour of cover:	silver
Max. flooring height:	25 mm
Load class:	K 3 (EN 1253-1)
Length:	138 mm
Width:	138 mm
Height:	16 mm
Locking:	screwed

Grating:

Rim length:	150 mm
Rim width:	150 mm
Rim material:	ABS

Upper section material:	ABS
-------------------------	-----