

Ecoguss drain body DN 70, Vertical outlet



Article information

Item no.: 48478
GTIN: 4026092033296
Price group: 40

Description

The Ecoguss base body is used in combination with an attachment piece for point drainage, and is equipped with a removable odor trap, and a protective cover for the construction period.

The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius.

The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Version:

| | |
|--|-------------------|
| System: | 125 |
| Odour trap: | included |
| Waterproofing layer on the drain body: | Connection flange |
| Sealing water height: | 50 mm |

General characteristics:

| | |
|----------------------|-----------|
| Nominal size (DN): | 70 |
| Outer diameter (OD): | 78 |
| Standard: | EN 1253-1 |

Dimensions:

| | |
|-----------|--------|
| Height: | 201 mm |
| Diameter: | 135 mm |

Tank:

Number of outlets: 1 ST

Drain body:

Material of drain body: Ecoguss

Socket version: vertical

Fire protection: Highest fire protection standards are reached using the optionally available Fire-Kit and Quick-Fit