

Parking deck drain, Ecoguss DN 125, round, Connection polymer pipe



Article information

Item no.: 48504
GTIN: 4026092036136
Price group: 40

Advantages

- Breakproof & load resistant
- Fulfils highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius

Description

The Ecoguss parking deck drain is used for point drainage and is equipped with a sludge bucket.

The recyclable composite material Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface.

Separate equipotential bonding is not necessary.

Version:

| | |
|--|-------------------|
| System: | 125 |
| Waterproofing layer on the drain body: | Connection flange |

General characteristics:

| | |
|----------------------|-----------|
| Nominal size (DN): | 125 |
| Outer diameter (OD): | 125 |
| Standard: | EN 1253-2 |

Dimensions:

| | |
|---------------------------|--------|
| Length: | 290 mm |
| Width: | 290 mm |
| Height: | 196 mm |
| Cutout dimension, length: | 300 mm |
| Cutout dimension, width: | 300 mm |

Coverage features:

| | |
|------------------|---------------------|
| Type of cover: | Round slotted cover |
| Cover material: | Ecoguss |
| Colour of cover: | black |
| Load class: | B 125 (EN 124) |
| Length: | 234 mm |
| Width: | 234 mm |
| Sludge bucket: | yes |
| Locking: | Lock & Lift |

Grating:

| | |
|--|---------|
| Rim length: | 247 mm |
| Rim width: | 247 mm |
| Rim material: | Ecoguss |
| Shape of upper section: | round |
| Upper section material: | Ecoguss |
| Discharge rate (l/s) with 20 mm backwater: | 4.5 l/s |