



Ecoguss project drain, press. fl. DN 70, horiz., Variofix, Slotted cover



Article information

Item no.: 48778.51
 GTIN: 4026092053225
 Price group: 40

Advantages

- Scientifically confirmed sound protection effect
- Highest fire protection standards

Description

The Ecoguss project drain is used for point drainage and is equipped with a pressure sealing flange as well as a removable odour trap, a lip seal and a temporary protective cover.

The recyclable composite material Ecoguss meets the highest noise protection requirements, is temperature-resistant, resistant to aggressive media, and has a permanently corrosion-free surface. It is also briefly flammable from 100 to 400 degrees Celsius.

The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary.

Version:

System:	125
Odour trap:	included
Type of waterproofing layer:	Waterproofing layer
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)

Sealing water height: 50 mm

General characteristics:

Nominal size (DN): 70
Outer diameter (OD): 78
Standard: EN 1253-1

Dimensions:

Length: 273 mm
Width: 273 mm

Tank:

Number of outlets: 1 ST

Drain body:

Material of drain body: Ecoguss
Socket version: lateral

Vertical adjustment: vertically adjustable upper section
Upper section: adjustable in three dimensions

Coverage features:

Type of cover: Slotted cover
Cover material: 304 stainless steel
Colour of cover: silver
Min. flooring height: 10 mm
Max. flooring height: 17 mm
Load class: K 3 (EN 1253-1)
Length: 138 mm
Width: 138 mm
Surface: Polished SST
Locking: screwed

Grating:

Rim length: 150 mm
Rim width: 150 mm
Rim material: 304 stainless steel

Shape of upper section: square

Upper section material:

ABS