

Linearis Comfort upper section L: 1050 mm, System 125, WaD, K 3



Article information

Item no.: 48931M GTIN: 4026092079072 Price group: 10

Advantages

- Individual design with reversible stainless steel insert
- Highest fire protection standards
- Low installation depth

Description

Used in combination with a drain body of the KESSEL 125 modular system, the Linearis Comfort upper section is suitable for use as indoor linear drainage.

Version:

System:	125
Odour trap:	included
Type of waterproofing layer:	Waterproofing layer
Seepage opening:	open
Waterproofing layer on the upper section:	Factory-fitted sealing collar (WaD) according to DIN
Water exposure class in accordance to DIN	18534
18534-1 (up to and including):	W3-I
Sealing water height:	50 mm
General characteristics: Nominal size (DN): Outer diameter (OD):	125 125
Dimensions: Width: Height: null:	243 mm 115 mm 1,115 mm



Coverage features:

Type of cover: Grating design: Cover material: Colour of cover: Load class: Surface: Locking:

Stainless steel cover optionally tileable 304 stainless steel silver, selectable K 3 (EN 1253-1) Brushed SST placed

Grating:

Rim length: Rim width: Rim material: 1,050 mm 66 mm 304 stainless steel

Shape of upper section: Upper section material: Discharge rate (l/s) with 10 mm backwater: Discharge rate (l/s) without backwater: square ABS 1.1 l/s 1 l/s