


## Linearis Comfort upper section L: 1150 mm, System 125, WaD, K 3



### Article information

Item no.: 48932M  
GTIN: 4026092079089  
Price group: 10

### Advantages

- Individual design with reversible stainless steel insert
- Highest fire protection standards
- Low installation depth

### Description

Used in combination with a drain body of the KESSEL 125 modular system, the Linearis Comfort upper section is suitable for use as indoor linear drainage.

#### Version:

System:	125
Odour trap:	included
Type of waterproofing layer:	Waterproofing layer
Seepage opening:	open
Waterproofing layer on the upper section:	Factory-fitted sealing collar (WaD) according to DIN 18534
Water exposure class in accordance to DIN 18534-1 (up to and including):	W3-I
Sealing water height:	50 mm

#### General characteristics:

Nominal size (DN):	125
Outer diameter (OD):	125

#### Dimensions:

Width:	243 mm
Height:	107 mm
null:	1,215 mm

**Coverage features:**

Type of cover:	Stainless steel cover
Grating design:	optionally tileable
Cover material:	304 stainless steel
Colour of cover:	silver, selectable
Load class:	K 3 (EN 1253-1)
Surface:	Brushed SST
Locking:	placed

**Grating:**

Rim length:	1,150 mm
Rim width:	66 mm
Rim material:	304 stainless steel
Shape of upper section:	square
Upper section material:	ABS
Discharge rate (l/s) with 10 mm backwater:	1.1 l/s
Discharge rate (l/s) without backwater:	1 l/s