


Light liquid trap DN 100, Slotted grating, with backwater protection



Article information

Item no.: 52101
 GTIN: 4026092029770
 Price group: 10

Advantages

- Blocks the path of light liquids in the event of an accident/emergency
- Including odour trap

Description

The light liquid trap made of polymer is suitable for floor slab installation and is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

Version:

Odour trap:	included
Sealing water height:	50 mm
Backwater protection:	Type 5
Number of mechanical backwater flaps:	2

General characteristics:

Nominal size (DN):	100
Outer diameter (OD):	110
Standard:	EN 1253-3, EN 1253-5, EN 13564

Dimensions:

Length:	320 mm
Width:	243 mm

Cutout dimension, length: 400 mm
Cutout dimension, width: 250 mm

Tank:

Installation depth: 216 - 276 mm

Drain body:

Material of drain body: Polymer

Vertical adjustment: vertically adjustable upper section
Vertical adjustment: 30 - 90 mm

Coverage features:

Type of cover: Slotted cover
Cover material: Polymer
Colour of cover: black
Load class: K 3 (EN 1253-1)
Length: 188 mm
Width: 188 mm
Sludge bucket: yes

Grating:

Rim length: 200 mm
Rim width: 200 mm

Upper section material: Polymer
Discharge rate (l/s) with 20 mm backwater: 1 l/s