


## Ferrofix drain body Sys 125, DN 70, Vert. outlet, Press. fl.



### Article information

Item no.: 54210  
GTIN: 4026092053676  
Price group: 70

### Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- Variably combinable with upper sections

### Description

In combination with a System 125 upper section, the Ferrofix stainless steel drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover.

The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only the sealing sheets tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes.

### Version:

System:	125
Odour trap:	included
Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)
Sealing water height:	50 mm

### General characteristics:

Nominal size (DN):	70
Outer diameter (OD):	78
Standard:	EN 1253-1

### Dimensions:

Length:	273 mm
Width:	273 mm

Height: 201 mm

**Tank:**

Number of outlets: 1 ST

**Drain body:**

Material of drain body: Stainless steel 14301  
Socket version: vertical