


Ferrofix floor drain DN 100, vertical, Slotted grating, SST



Article information

Item no.: 54430.20
 GTIN: 4026092056479
 Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel

Description

The Ferrofix stainless steel floor drain is used for point drainage and is equipped with a removable odour trap made of stainless steel, a lip seal and a temporary protective cover.

The outlet socket is suitable for connection to SML cast iron pipes.

Version:

| | |
|---|-------------------|
| System: | 125 |
| Odour trap: | included |
| Waterproofing layer on the upper section: | Connection flange |
| Waterproofing layer on the drain body: | Connection flange |
| Sealing water height: | 50 mm |

General characteristics:

| | |
|----------------------|-----------|
| Nominal size (DN): | 100 |
| Outer diameter (OD): | 110 |
| Standard: | EN 1253-1 |

Dimensions:

Length: 142 mm
Width: 142 mm

Tank:

Number of outlets: 1 ST

Drain body:

Material of drain body: Stainless steel 14301
Socket version: vertical

Vertical adjustment: vertically adjustable upper section
Upper section: vertically adjustable

Coverage features:

Type of cover: Slotted grating
Cover material: Stainless steel 14301
Load class: L 15 (EN 1253-1)
Length: 138 mm
Width: 138 mm
Locking: unlocked

Grating:

Rim length: 150 mm
Rim width: 150 mm

Upper section material: Stainless steel 14301