


Ferrofix floor drain DN 100, vertical, Slotted grating



Article information

Item no.: 54430.61
 GTIN: 4026092053485
 Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel

Description

The Ferrofix stainless steel floor drain is used for point drainage and is equipped with a removable odour trap made of stainless steel, a lip seal and a temporary protective cover.

The outlet socket is suitable for connection to SML cast iron pipes.

Version:

System:	125
Odour trap:	included
Waterproofing layer on the upper section:	Connection flange
Waterproofing layer on the drain body:	Connection flange
Sealing water height:	50 mm

General characteristics:

Nominal size (DN):	100
Outer diameter (OD):	110
Standard:	EN 1253-1

Dimensions:

Length: 142 mm
Width: 142 mm

Tank:

Number of outlets: 1 ST

Drain body:

Material of drain body: Stainless steel 14301
Socket version: vertical

Vertical adjustment: vertically adjustable upper section
Upper section: vertically adjustable

Coverage features:

Type of cover: Slotted cover
Cover material: Stainless steel 14301
Load class: L 15 (EN 1253-1)
Length: 138 mm
Width: 138 mm
Locking: screwed

Grating:

Rim length: 150 mm
Rim width: 150 mm

Upper section material: ABS