

Ferrofix floor drain Sys 200, horiz., Slotted grating



Article information

Item no.: 55350.20
GTIN: 4026092009949
Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel

Description

The Ferrofix stainless steel floor drain is used for point drainage and is equipped with a removable odour trap, a lip seal and a temporary protective cover.

The outlet socket is suitable for connection to SML cast iron pipes.

Version:

| | |
|---|-------------------|
| System: | 200 |
| Odour trap: | included |
| Waterproofing layer on the upper section: | Connection flange |
| Waterproofing layer on the drain body: | Connection flange |
| Sealing water height: | 70 mm |

General characteristics:

| | |
|----------------------|-----------|
| Nominal size (DN): | 100 |
| Outer diameter (OD): | 110 |
| Standard: | EN 1253-1 |

Dimensions:

| | |
|---------|--------|
| Length: | 280 mm |
| Width: | 280 mm |

Tank:

| | |
|--------------------|------|
| Number of outlets: | 1 ST |
|--------------------|------|

Drain body:

| | |
|-------------------------|-------------------------------------|
| Material of drain body: | Stainless steel 14301 |
| Socket version: | lateral |
| Vertical adjustment: | vertically adjustable upper section |
| Upper section: | vertically adjustable |

Coverage features:

| | |
|-----------------|-----------------------|
| Type of cover: | Slotted grating |
| Cover material: | Stainless steel 14301 |
| Load class: | M 125 (EN 1253-1) |
| Length: | 190 mm |
| Width: | 190 mm |
| Height: | 30 mm |
| Surface: | pickled |
| Locking: | unlocked |

Grating:

| | |
|-------------------------|-----------------------|
| Rim length: | 200 mm |
| Rim width: | 200 mm |
| Shape of upper section: | square |
| Upper section material: | Stainless steel 14301 |