

Ferrofix renovation drain DN 50, horizontal, Slot grt, K 3



Article information

Item no.: 59325
GTIN: 4026092103036
Price group: 70

Advantages

- Made of particularly hygienic and mechanically highly resistant stainless steel
- ideal for the food industry
- catering kitchens and swimming pools
- Including odour trap

Description

The Ferrofix stainless steel renovation drain is equipped with a horizontal outlet DN 50 as well as a removable odour trap.

Version:

| | |
|---|-------------------|
| System: | 125 |
| Odour trap: | included |
| Waterproofing layer on the upper section: | Connection flange |
| Sealing water height: | 50 mm |

General characteristics:

| | |
|----------------------|----|
| Nominal size (DN): | 50 |
| Outer diameter (OD): | 50 |

Dimensions:

| | |
|---------------------|--------|
| Length: | 223 mm |
| Width: | 148 mm |
| Height: | 100 mm |
| Max. design height: | 100 mm |

Tank:

| | |
|--------------------|------|
| Number of outlets: | 1 ST |
|--------------------|------|

Drain body:

Material of drain body: Stainless steel 14301
Socket version: lateral

Coverage features:

Type of cover: Slotted cover
Cover material: 304 stainless steel
Load class: K 3 (EN 1253-1)
Length: 138 mm
Width: 138 mm
Locking: screwed

Grating:

Rim length: 148 mm
Rim width: 148 mm

Upper section material: Stainless steel 14301
Discharge rate (l/s) with 20 mm backwater: 0.8 l/s