

Yard drain System 200, vert., Slotted grating, B 125



Article information

Item no.: 67922B
 GTIN: 4026092038833
 Price group: 10

Advantages

- Recyclable
- Fulfils highest sound protection requirements
- Temperature-resistant up to 400 degrees Celsius
- Permanently corrosion-free surface

Description

The Ecoguss yard drain is used for point drainage and is equipped with a sludge bucket.

The recyclable composite material, Ecoguss fulfils the highest sound protection requirements, can withstand temperatures up to 400 degrees Celsius and has a permanently corrosion-free surface.

The outlet socket is suitable for connection to polymer pipes. Separate equipotential bonding is not necessary.

Version:

System:	200
Odour trap:	no

General characteristics:

Nominal size (DN):	100
--------------------	-----

Tank:

Number of outlets:	1 ST
--------------------	------

Drain body:

Material of drain body:	Polymer
-------------------------	---------

Socket version: vertical

Vertical adjustment: 40 - 150 mm

Coverage features:

Type of cover: Round slotted cover
Cover material: Ecoguss
Colour of cover: black
Load class: B 125 (EN 124)
Length: 258 mm
Width: 258 mm
Surface: EDM
Sludge bucket: yes
Locking: Lock & Lift

Grating:

Rim length: 258 mm
Rim width: 258 mm
Rim material: Ecoguss

Shape of upper section: square
Upper section material: Ecoguss
Discharge rate (l/s) with 20 mm backwater: 4.5 l/s