

Backwater valve Staufix Basic DN 125, Type 1, with emergency closure



Article information

Item no.: 72125
 GTIN: 4026092002360
 Price group: 10

Advantages

- Simple conversion possible using conversion kits
- Optional rat protection flap for additional safety
- Fast and toolless maintenance and cleaning

Description

The backwater valve for wastewater without sewage is equipped with one mechanical flap which closes automatically in the event of backwater and also serves as an emergency closure to be closed by hand.

Thanks to the modular KESSEL system, existing systems can easily be supplemented by a second backwater flap.

| | |
|-------------------------|---------------------------|
| Type of wastewater: | wastewater without sewage |
| Installation situation: | exposed drainage pipe |

Version:

| | |
|---|--------------------|
| Stainless steel flap as rat protection: | no |
| Emergency closure: | yes |
| Delivery state: | installation-ready |
| Backwater protection: | Type 1 |
| Number of mechanical backwater flaps: | 1 |

General characteristics:

| | |
|----------------------|----------|
| Nominal size (DN): | 125 |
| Outer diameter (OD): | 125 |
| Standard: | EN 13564 |

Dimensions:

| | |
|---------|--------|
| Length: | 405 mm |
| Width: | 200 mm |
| Height: | 280 mm |

| | |
|---|-----------------------|
| Vertical drop between inlet and outlet: | 9 mm |
| Cover locking: | Quick-release closure |