
IK KESSEL

Controlfix clean out DN 100, Floor slab, black





Article information

Item no.: 80100S GTIN: 4026092004050 Price group: 30

Advantages

- Simple conversion to Staufix SWA
- Staufix FKA or Pumpfix F
- Fast
- toolless access for cleaning
- Available as a complete set or module set

Description

The Premium clean out for faecal and faecal-free wastewater makes easy access to wastewater pipes possible for inspection and maintenance work.

Thanks to the modular KESSEL system, existing systems can easily be converted to a Staufix SWA Premium backwater valve, Staufix FKA or Pumpfix F backwater pumping station. Type of wastewater: Installation situation: wastewater with and without sewage floor slab installation

Version:

Type of waterproofing layer:

Delivery state:

Waterproofing layer

Installation-ready (connection parts must be connected on site)

General characteristics:

Nominal size (DN): Outer diameter (OD): Colour: 100 110 black



Dimensions:

Length:	486 mm
Width:	590 mm
Cutout dimension, length:	750 mm
Cutout dimension, width:	750 mm

Tank:

Installation depth:	486 - 640 mm
Groundwater resistant from lower edge of base	3,000 mm
section:	

Drain body:

Socket version:

Vertical adjustment:

vertically adjustable upper section

including spigot and socket

Coverage features:

Type of cover:
Cover material:
Colour of cover:
Load class:
Length:
Width:
Tightness:
Locking:

Cover plate Polymer black L 15 (EN 1253-1) 366 mm 366 mm surface water resistant Lock & Lift

Vertical drop between inlet and outlet:

9 mm