


Pumping station Aquapump Medium Mono, GTF1200, 1300-1750 mm, B



Article information

Item no.: 827820B
 GTIN: 4026092045732
 Price group: 60

Advantages

- Maximum safety
- Flexible installation
- LW 600 chamber system suitable for underground installation

Description

The pumping station for faecal-free wastewater is equipped with a submersible pump and a backflow preventer. The collection tank is an LW 600 chamber system made of permanently resistant polymer (PE-LLD) with open pump tank and universal connection options. Quick-release closures enable the integrated components to be removed easily.

The station is optionally controlled by a user-friendly control unit, which can be integrated in the building management system via a potential-free contact. Alternatively, alarm and collective fault messages can be output via a GSM interface.

Type of wastewater:	wastewater without sewage
Installation situation:	underground installation

Version:

Type of system:	Single station
Installation:	Wet installation
Pump control:	Float switch
Backflow preventer:	integrated
Passage seal for ventilation pipe (DN):	100 mm
Passage seal for conduit pipe (DN):	100 mm

Delivery state:

Modular set for assembly on site

General characteristics:

Colour: grey
Standard: EN 12050-2

Dimensions:

Length: 806 mm
Width: 806 mm

Tank:

Number of inlets: 1 ST
Inlet nominal size (DN): 150
Inlet nominal size (OD): 160 mm
Distance pipe bottom inlet to tank bottom: 400 mm
Distance from centre of outlet pipe to tank bottom: 894 mm
Distance from centre of inlet pipe to tank bottom: 455 mm
Connection conduit pipe (DN): 100 mm
Pressure pipe connection: horizontal
Pressure pipe connection (DN): 32 mm
Pressure pipe connection (OD): 40 mm
Installation depth: 1,300 - 1,750 mm
Venting connection (DN): 100 mm
Groundwater resistant from lower edge of base section: 2,000 mm
Clear width of tank (LW): 600 mm
Clear width of entry (LW): 600 mm
Chamber system: LW 600

Vertical adjustment: vertically adjustable upper section

Coverage features:

Type of cover: Round cover plate
Cover material: Grey iron
Colour of cover: black
Load class: B 125 (EN 124)
Length: 648 mm
Width: 648 mm
Height: 103 mm
Locking: unlocked

Pumping device:

Pump:	GTF 1200
Number of pumps:	1
Max. pumping capacity:	15.5 m ³ /h
Max. pumping height:	9 m
Operating mode:	S3 - 50 %
Power P1:	1.4 kW
Power P2:	0.84 kW
Speed:	2,650 U/min
Type of fuse required (electrical protection):	C 16 A
Max. temperature (permanent) of conveyed material:	40 °C
Connection type:	Schuko (earthed contact) 2-pin
Weight:	10 kg
Impeller type:	Multi-vane impeller
Length of mains cable for pump:	10 m
Rated current:	6.2 A
Protection class (pump):	IP 68 (3m)
Protection class:	I
Type of pump connection cable:	H07RN-F 3G 1.0 mm ²
Temperature monitoring:	integrated
Cos phi - power factor:	0.98
Insulation class:	F

Control:

Operating voltage:	230 V
Mains frequency:	50 Hz
Type of level measurement:	mechanical
Level measurement instrument:	Float switch