

Yard drain System 400, DN 100, B, 730 - 1080 mm



Article information

Item no.: 851102B
GTIN: 4026092004326
Price group: 10

Advantages

- Different load classes available
- Height-adjustable complete system
- Easy underground installation

Description

The polymer yard drain is used for point drainage and is resistant to aggressive wastewater. It is equipped with a sludge bucket and fuel resistant seals.

The polymer upper section enables continuous height and level adjustment.

Version:

| | |
|-----------------------|----------|
| System: | 400 |
| Odour trap: | included |
| Sealing water height: | 100 mm |

General characteristics:

| | |
|--------------------|--------|
| Nominal size (DN): | 100 |
| Colour: | black |
| Standard: | EN 752 |

Dimensions:

| | |
|---------------------------|--------|
| Cutout dimension, length: | 585 mm |
| Cutout dimension, width: | 535 mm |
| Min. insertion depth: | 55 mm |

Tank:

| | |
|---------------------|----------------|
| Number of outlets: | 1 ST |
| Installation depth: | 730 - 1,080 mm |

Groundwater resistant from lower edge of base section: 500 mm

Drain body:

Material of drain body: Polymer
Socket version: lateral

Vertical adjustment: vertically adjustable upper section

Coverage features:

Type of cover: Round slotted cover
Cover material: Grey iron
Colour of cover: black
Load class: B 125 (EN 124)
Length: 400 mm
Width: 400 mm
Surface: EDM
Sludge bucket: yes

Grating:

Rim length: 400 mm
Rim width: 400 mm

Shape of upper section: square
Discharge rate (l/s) with 20 mm backwater: 4.5 l/s