

Grease separat. EasyClean Modular free, NS 1, Direct, 3-part



Article information

Item no.: 93001.00/D1-R2

GTIN: 4026092103647

Price group: 60

Advantages

- Ideal where access is tight
- can be divided into 3 parts for insertion, for an insertion opening of max. 66 cm
- Direct disposal with the tank closed

Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work.

A direct disposal pipe socket is available for odour-reduced manual disposal.

20 year polyethylene warranty.

Installation situation:

free-standing set-up

Version:

Type of disposal:	manual
Disposal system:	Disposal connection
Disposal variant:	Direct
Refill inlet in accordance with DIN 1988:	no
Nominal size (NS):	1
Inspection window:	no
Shredder-Mix-System:	no
SonicControl:	no

Delivery state:

Installation-ready (connection parts must be connected on site)

General characteristics:

Material: PE
Standard: EN 1825

Dimensions:

Set-up area, height: 1,236 mm
Required access area, length: 1,120 mm
Required access area, width: 1,020 mm
Required access area, height: 500 mm
Height tank bottom up to centre section: 485 mm
Height centre section: 200 mm
Height centre section to top edge of tank: 445 mm

Tank:

Inlet nominal size (DN): 100
Inlet nominal size (OD): 110 mm
Outlet nominal size (DN): 100
Outlet nominal size (OD): 110 mm
Distance pipe bottom inlet to tank bottom: 850 mm
Distance pipe bottom outlet to tank bottom: 780 mm
Chamber system: three-piece chamber
Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

Coverage features:

Type of cover: Cover
Cover material: Polymer
Colour of cover: black
Tightness: odour-tight
Locking: Quick-release closure

Wastewater contents:

Separator contents: 230 l
Total volume: 330 l
Contents of sludge trap: 100 l
Storage quantity of grease: 80 l

Control:

Control unit:

no