

# Grease separat. EasyClean Modular free, NS 3, Standard, 2-part

## Article information

Item no.: 93003-R GTIN: 4026092071243 Price group: 60

# **Advantages**

- Ideal where access is tight
- can be divided into several parts for insertion, for an insertion opening of max. 66 cm
- Low-maintenance operation

# Description

The separator for greasy wastewater is suitable for free-standing set-up in frostprotected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank (NS 0.5 with two tanks) made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work.

Manual disposal is carried out with the tank open.

20 year polyethylene warranty. Installation situation:

free-standing set-up

### Version:

Type of disposal: Disposal variant: Refill inlet in accordance with DIN 1988: Nominal size (NS): Inspection window: Shredder-Mix-System: SonicControl:	manual with suction hose Standard no 3 no no no
Delivery state:	Installation-ready (connection parts must be connected on site)
General characteristics:	
Material:	PE
Dimensions:	
Set-up area, height:	1,395 mm

Required access area, length:

1,100 mm



Required access area, width:1,020 mmRequired access area, height:690 mmHeight tank bottom up to centre section:650 mmHeight centre section to top edge of tank:690 mm

#### Tank:

Inlet nominal size (DN): 100 110 mm Inlet nominal size (OD): Outlet nominal size (DN): 100 Outlet nominal size (OD): 110 mm Distance pipe bottom inlet to tank bottom: 1,090 mm Distance pipe bottom outlet to tank bottom: 1,020 mm Chamber system: two-piece chamber Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

#### **Coverage features:**

Type of cover:	Cover	
Cover material:	Polymer	
Colour of cover:	black	
Tightness:	odour-tight	
Locking:	Quick-release closure	

#### Wastewater contents:

Separator contents:	300 l
Total volume:	600 l
Contents of sludge trap:	300 l
Storage quantity of grease:	120 l

#### Control:

Control unit:

no