

## Grease separat. EasyClean Modular free, NS 3, round, Direct disposal



### Article information

Item no.: 93003.00/D1-R  
 GTIN: 4026092103654  
 Price group: 60

### Advantages

- Ideal where access is tight
- can be divided into 3 parts for insertion, for an insertion opening of max. 66 cm
- Direct disposal with the tank closed

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. Thanks to the modular design, the separator can be inserted even where access is extremely tight. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap. A service access cover with odour-tight cover and quick-release closures makes easy access possible for cleaning and maintenance work.

A direct disposal pipe socket is available for odour-reduced manual disposal.

20 year polyethylene warranty.

Installation situation: free-standing set-up

### Version:

Type of disposal:	manual
Disposal system:	Disposal connection
Disposal variant:	Direct
Nominal size (NS):	3
Delivery state:	Installation-ready (connection parts must be connected on site)
Scope of delivery:	Storz-B coupling R 2 1/2" for disposal vehicle connection

### General characteristics:

Material:	PE
Standard:	EN 1825

**Dimensions:**

Set-up area, height:	1,395 mm
Required access area, length:	1,020 mm
Required access area, width:	1,100 mm
Required access area, height:	690 mm

**Tank:**

Inlet nominal size (DN):	100
Outlet nominal size (DN):	100
Chamber system:	two-piece chamber

**Coverage features:**

Type of cover:	Cover
Tightness:	odour-tight
Locking:	Quick-release closure

**Wastewater contents:**

Separator contents:	300 l
Contents of sludge trap:	300 l