

## Grease separator EasyClean free NS 10, Direct, Insp. Wind., SonicControl



### Article information

Item no.: 93010.22/D  
GTIN: 4026092063668  
Price group: 60

### Advantages

- Direction of flow can be changed thanks to self-sealing interchangeable hubs
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has a tapered base for fast and clean disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

A direct disposal pipe socket is available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank.

20 year polyethylene warranty.

Installation situation: free-standing set-up

### Version:

Type of disposal:	manual
Disposal system:	Disposal connection
Disposal variant:	Direct
Refill inlet in accordance with DIN 1988:	no
Nominal size (NS):	10
Inspection window:	yes
Shredder-Mix-System:	no
SonicControl:	yes
Load-bearing capacity (DIN 19901):	F3
Delivery state:	Installation-ready (connection parts must be connected on site)

Scope of delivery: Storz-B coupling R 2 1/2" for disposal vehicle connection

### General characteristics:

Material: PE  
Standard: EN 1825

### Dimensions:

Set-up area, length: 2,822 mm  
Set-up area, width: 973 mm  
Set-up area, height: 1,653 mm  
Required access area, length: 2,590 mm  
Required access area, width: 940 mm  
Required access area, height: 1,653 mm

### Tank:

Inlet nominal size (DN): 150  
Inlet nominal size (OD): 160 mm  
Outlet nominal size (DN): 150  
Outlet nominal size (OD): 160 mm  
Distance pipe bottom inlet to tank bottom: 1,255 mm  
Distance pipe bottom outlet to tank bottom: 1,185 mm  
Pressure pipe connection (DN): 65 mm  
Pressure pipe connection (OD): 75 mm  
Nominal pressure (PN): 10  
Connection inlet/outlet sockets: PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

### Coverage features:

Type of cover: Cover  
Cover material: Polymer  
Colour of cover: violet  
Tightness: odour-tight  
Locking: Quick-release closure

### Wastewater contents:

Separator contents: 900 l  
Total volume: 1,900 l  
Contents of sludge trap: 1,000 l  
Storage quantity of grease: 400 l

**Control:**

Control unit: no