

## EasyClean round grease separator free, NS 20, Standard



### Article information

Item no.: 93020.05

GTIN:

Price group: 60

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and is manufactured without the need for metallic internal structural components. The collection tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has sloped sides in the base to promote fast and efficient disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work.

Manual disposal takes place with the tank open.

20 year polyethylene warranty.

Installation situation:

free-standing set-up

### Version:

Type of disposal:

manual with suction hose

Disposal variant:

Standard

Refill inlet in accordance with DIN 1988:

no

Nominal size (NS):

20

Inspection window:

no

Shredder-Mix-System:

no

SonicControl:

no

Load-bearing capacity (DIN 19901):

F3

Delivery state:

Installation-ready (connection parts must be connected on site)

### General characteristics:

Material:

PE

Standard:

EN 1825

**Dimensions:**

Set-up area, length:	2,230 mm
Set-up area, width:	1,922 mm
Set-up area, height:	2,300 mm
Required access area, length:	2,230 mm
Required access area, width:	1,880 mm
Required access area, height:	2,300 mm

**Tank:**

Inlet nominal size (DN):	200
Inlet nominal size (OD):	200 mm
Outlet nominal size (DN):	200
Outlet nominal size (OD):	200 mm
Distance pipe bottom inlet to tank bottom:	1,920 mm
Distance pipe bottom outlet to tank bottom:	1,850 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

**Coverage features:**

Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	black
Tightness:	odour-tight
Locking:	Quick-release closure

**Wastewater contents:**

Separator contents:	2,650 l
Total volume:	4,650 l
Contents of sludge trap:	2,000 l
Storage quantity of grease:	800 l

**Control:**

Control unit:	no
---------------	----