

## Grease separator EasyClean free Basic, NS 7, Direct, left



### Article information

Item no.: 94007.10DL  
GTIN: 4026092084151  
Price group: 60

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and comes without metallic components in the tank. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap.

Two odour-tight covers with quick-release closures allow for easy access for cleaning and maintenance work.

There is a direct disposal pipe socket available for odour-reduced manual disposal. After disposal, a maximum of 3 litres residual sludge volume is left in the tank.

20 year polyethylene warranty.

Installation situation: free-standing set-up

### Version:

|   |        |
|---|--------|
| Type of disposal:                         | manual |
| Disposal variant:                         | Direct |
| Refill inlet in accordance with DIN 1988: | no     |
| Nominal size (NS):                        | 7      |
| Inspection window:                        | no     |
| Load-bearing capacity (DIN 19901):        | F3     |

Delivery state: Installation-ready (connection parts must be connected on site)

Scope of delivery: Storz-B coupling R 2 1/2" for disposal vehicle connection

### General characteristics:

Material: PE

Standard: EN 1825

### Dimensions:

|                               |          |
|-------------------------------|----------|
| Set-up area, length:          | 1,960 mm |
| Set-up area, width:           | 1,020 mm |
| Set-up area, height:          | 1,670 mm |
| Required access area, length: | 1,960 mm |
| Required access area, width:  | 920 mm   |
| Required access area, height: | 1,670 mm |

### Tank:

|   |   |
|---|---|
| Inlet nominal size (DN):                    | 150   |
| Inlet nominal size (OD):                    | 160 mm  |
| Outlet nominal size (DN):                   | 150   |
| Outlet nominal size (OD):                   | 160 mm  |
| Distance pipe bottom inlet to tank bottom:  | 1,255 mm  |
| Distance pipe bottom outlet to tank bottom: | 1,185 mm  |
| Pressure pipe connection (DN):              | 65 mm   |
| Pressure pipe connection (OD):              | 75 mm   |
| Nominal pressure (PN):                      | 10  |
| Connection inlet/outlet sockets:            | PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS |

### Coverage features:

|                  |                       |
|------------------|-----------------------|
| Type of cover:   | Cover                 |
| Cover material:  | Polymer               |
| Colour of cover: | violet                |
| Tightness:       | odour-tight           |
| Locking:         | Quick-release closure |

### Wastewater contents:

|                              |         |
|------------------------------|---------|
| Total volume:                | 1,370 l |
| Contents of sludge trap:     | 700 l   |
| Storage quantity of grease:  | 280 l   |
| Max. grease layer thickness: | 230 mm  |