

EasySink sediment separator ground, NS 1, Class D



Article information

Item no.: 97201/00D
GTIN: 4026092026861
Price group: 60

Advantages

- Waterproof
- resistant to aggressive wastewater
- Odour-tight tank
- Vertically adjustable upper section with odour-tight cover plates with different load classes

Description

The sediment separator is suitable for installation in the ground. The collection tank made of permanently resistant polymer (PE) is equipped with a removable sediment tank (NS 2 with two sediment tanks) made of stainless steel and a hole diameter of 5 mm. An odour trap is installed in the outlet. Access for cleaning and maintenance work is possible via one or several service access covers.

20 year polyethylene warranty.

Options:

Hole diameter of sediment tank:	3, 6, 8, 10, 12, 15 mm
Additional price for additional fine screen (mesh size 1.0 mm)	
Installation situation:	underground installation

Version:

Type of disposal:	manual with suction hose
Odour trap:	included
Nominal size (NS):	1
Load-bearing capacity (DIN 19901):	E4
Delivery state:	Installation-ready (connection parts must be connected on site)

General characteristics:

Material:	PE
-----------	----

Dimensions:

Required access area, length:	1,100 mm
Required access area, width:	532 mm

Tank:

Inlet nominal size (DN):	100
Inlet nominal size (OD):	110 mm
Outlet nominal size (DN):	100
Outlet nominal size (OD):	110 mm
Distance pipe bottom inlet to tank bottom:	528 mm
Distance pipe bottom outlet to tank bottom:	380 mm
Installation depth:	55 - 405 mm
Groundwater resistant from lower edge of base section:	500 mm
Clear width of entry (LW):	400 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS
Vertical adjustment:	vertically adjustable upper section, can be tilted by 5 degrees

Coverage features:

Type of cover:	Cover plate
Cover material:	Grey iron
Colour of cover:	black
Load class:	D 400 (EN 124)
Length:	395 mm
Width:	395 mm
Height:	52 mm
Tightness:	odour-tight and surface water resistant
Locking:	locked

Control:

Control unit:	no
Volume of collecting tank:	12 l