

EasyOil oil/fuel separator NS 10, Class II, 2600 l, B, In/outlet PE



Article information

Item no.: 99610.15BEX

GTIN:

Price group: 60

Description

The separator for light liquids is suitable for installation in the ground. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and an automatic closure device. One or more surface water resistant covers makes easy access possible for cleaning and maintenance work.

A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL AG.

20 year polyethylene warranty.

Version:

Type of disposal:	manual with suction hose
Coalescence insert:	no
Nominal size (NS):	10
Load-bearing capacity (DIN 19901):	E2
Separator class:	II

Dimensions:

Max. length:	3,162 mm
Required access area, length:	2,910 mm
Required access area, width:	1,200 mm
T-DSC:	155 mm
DSC:	700 - 1,800 mm
Excess depth:	100 mm

Tank:

Inlet nominal size (DN):	150
Inlet nominal size (OD):	160 mm
Outlet nominal size (DN):	150
Outlet nominal size (OD):	160 mm
Distance pipe bottom inlet to tank bottom:	1,110 mm
Distance pipe bottom outlet to tank bottom:	1,070 mm
Installation depth:	840 - 1,240 mm
Groundwater resistant from lower edge of base section:	1,320 mm
Clear width of entry (LW):	600 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS

Coverage features:

Type of cover:	Cover plate
Cover material:	Grey iron
Colour of cover:	black
Load class:	B 125 (EN 124)
Length:	648 mm
Width:	648 mm
Height:	95 mm
Tightness:	odour-tight and surface water resistant
Locking:	unlocked

Wastewater contents:

Total volume:	2,600 l
Contents of sludge trap:	1,500 l
Storage quantity of light liquid:	267 l

Control:

Control unit:	no
---------------	----