

EasyOil oil/fuel separator NS 15, Class II, 5800 l, B, In/outlet PE



Article information

Item no.: 99615.80BEX

GTIN:

Price group: 60

Description

The separator for light liquids is suitable for installation in the ground. The collecting tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and an automatic closure device. One or more surface water resistant covers makes easy access possible for cleaning and maintenance work.

A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL AG.

20 year polyethylene warranty.

Version:

| | |
|------------------------------------|--------------------------|
| Type of disposal: | manual with suction hose |
| Coalescence insert: | no |
| Nominal size (NS): | 15 |
| Load-bearing capacity (DIN 19901): | E2 |
| Separator class: | II |

Dimensions:

| | |
|-------------------------------|----------------|
| Max. length: | 3,460 mm |
| Required access area, length: | 3,110 mm |
| Required access area, width: | 1,760 mm |
| T-DSC: | 180 mm |
| DSC: | 700 - 1,800 mm |
| Excess depth: | 130 mm |

Tank:

| | |
|--|---|
| Inlet nominal size (DN): | 200 |
| Inlet nominal size (OD): | 200 mm |
| Outlet nominal size (DN): | 200 |
| Outlet nominal size (OD): | 200 mm |
| Distance pipe bottom inlet to tank bottom: | 1,630 mm |
| Distance pipe bottom outlet to tank bottom: | 1,600 mm |
| Installation depth: | 870 - 1,250 mm |
| Groundwater resistant from lower edge of base section: | 1,810 mm |
| Clear width of entry (LW): | 600 mm |
| Connection inlet/outlet sockets: | PE-HD pipes in accordance with DIN 19537, PVC-KG pipes in accordance with DIN 19534, PP or AS |

Coverage features:

| | |
|------------------|---|
| Type of cover: | Cover plate |
| Cover material: | Grey iron |
| Colour of cover: | black |
| Load class: | B 125 (EN 124) |
| Length: | 648 mm |
| Width: | 648 mm |
| Height: | 95 mm |
| Tightness: | odour-tight and surface water resistant |
| Locking: | unlocked |

Wastewater contents:

| | |
|-----------------------------------|---------|
| Total volume: | 5,800 l |
| Contents of sludge trap: | 5,000 l |
| Storage quantity of light liquid: | 470 l |

Control:

| | |
|---------------|----|
| Control unit: | no |
|---------------|----|