Backwater valves

Accessories

Staufix

Extension sections

made of polymer



for deeper installation

Inclusive: Sealing Extension: Max. 147 mm

Note: In case of deeper installation ensure maintenance capability!

Art. no. 830 070





with flange

for installation in waterproof concrete

Inclusive sealing set:

Elastomer waterproofing membrane

made of NK/SBR Ø 700 mm

Extension: Max. 294 mm

Delivery: Completely assembled. Note: Suitable for installation in the concrete slab/floor.

Art. no. 830 075

with flange with flange and counter flange

for deeper installation

Material: Counter flange made of stainless steel **Inclusive:** Sealing Extension: Max. 147 mm Compatibility: For connection to an on-site membrane Note: In case of deeper installation ensure maintenance capability!

Art. no. 830 073

Spigot / Socket

made of polymer



Spigot

removable sides and in different dimensions

fitting mountable on both	

Outer diameter Ø (mm)	Art. no.
Ø 90	83 090
Й 100	830 200



Socket

removable fitting mountable on both sides and in different dimensions

Outer diameter Ø (mm)	Art. no.	Outer diameter Ø (mm)	Art. no.
Ø 90	83 090	Ø 90	83 091
Ø 100	830 200	Ø 100	830 202
Ø 110	830 100	Ø 110	830 101
Ø 125	83 082	Ø 125	83 086
Ø 160	83 083	Ø 160	83 087
Ø 200	83 084	Ø 200	83 084