

Accessories

Upper section

Art. no.

Upper section

Compatibility: For pumping station *Aquapump Basic*
Extension: From 140 - 440 mm, height adjustable;
 two can also be installed on top of each other



829 100

Closure valves

Art. no.

Closure valve

Compatibility: For pumping station *Aquapump Basic Mono* version



829 200

Closure valve

Compatibility: For pumping station *Aquapump Basic Duo* version




829 250

Alarm unit

Art. no.

with electrode probe


Compatibility: For pumping station *Aquapump Basic*, engineering system base *Aquapump XL*
Function: High water / flood alarm system; for conductive liquids
Inclusive: Visual and audible alarm warning, battery back up, with Logbook, connection for remote alarm speaks (Art. no. 20 162) or upgradable with potential free contact.
Voltage: 230 V ~ 50 Hz (IP 54)
Plug: 2 pin grounded
Cable length: 5 m (extendable up to 30 m)



20 222

with optical probe

Compatibility: For pumping station *Aquapump Basic*, engineering system base *Aquapump XL*
Function: High water / flood alarm system; for conductive / non-conductive liquids
Inclusive: Visual and audible alarm warning, battery back up, with Logbook, connection for remote alarm speaks (Art. no. 20 162) or upgradable with potential free contact.
Voltage: 230 V ~ 50 Hz (IP 54)
Plug: 2 pin grounded
Cable length: 5 m (extendable up to 30 m)



20 223

Cable length: 10 m (extendable up to 30 m)

20 224

Potential-free contact

Compatibility:
 For warning devices Art. no. 20 222 and 20 223



80 074