

Floor drain *Practicus*

with slotted cover in ABS

System 125



EN 1253-1

Made in PP, with removable odour trap, sealing water height 50 mm, with lip seal. Drainage capacity in l/sec with 20 mm / 10 mm threshold lateral outlet: 1.6 l/sec / 1.1 l/sec vertical outlet: 2.0 l/sec / 1.0 l/sec.

Installation area:

lateral outlet: 220 × 180 mm

vertical outlet: 180 × 180 mm

With upper section in ABS

slotted cover 138 × 138 mm in ABS,

black, class K 3



Illustration shows Art. no. 45 110.40 (lateral outlet)




Illustration shows Art. no. 45 110.40 (lateral outlet)




Illustration shows Art. no. 45 210.40 (vertical outlet)

Outer diameter Ø (mm)	Art. no.
Lateral outlet	
Ø 110	45 110.40
Vertical outlet	
Ø 110	45 210.40

Floor drain *Practicus*

with slotted cover in stainless steel AISI 304

System 125



EN 1253-1


Made in PP, with removable odour trap, sealing water height 50 mm, vertical outlet, with lip seal. Drainage capacity in l/sec with 20 mm / 10 mm threshold Ø 110: 2.0 l/sec / 1.0 l/sec.

Installation area 180 × 180 mm

With upper section in ABS,

slotted cover 138 × 138 mm in stainless

steel AISI 304, screwed, class K 3



Outer diameter Ø (mm)	Art. no.
Ø 50	45 250.11
Ø 75	45 270.11
Ø 110	45 210.11